


Specifications


Current Rating :	3.0 Ampere
Insulation Resistance :	1000 MΩ Min
Dielectric Withstanding :	600V AC
Contact Resistance :	20 mΩ Max
Operating Temperature :	-40°C to +105°C

Materials


Contact Material :	Phosphor Bronze
Insulation Material :	High Temperature Thermoplastic, 94V-0 PBT



Mating with



P.S. : Suggested mating pin length : 4.0 ~ 6.0 mm



No. of Pins/Row	Dimension Information		No. of Pins/Row	Dimension Information		No. of Pins/Row	Dimension Information		No. of Pins/Row	Dimension Information	
	C	D		C	D		C	D		C	D
04	7.62	10.66	11	25.40	28.44	21	50.80	53.84	31	76.20	79.24
05	10.16	13.20	12	27.94	30.98	22	53.34	56.38	32	78.74	81.78
06	12.70	15.74	13	30.48	33.52	23	55.88	58.92	33	81.28	84.32
07	15.24	18.28	14	33.02	36.06	24	58.42	61.46	34	83.82	86.86
08	17.78	20.82	15	35.56	38.60	25	60.96	64.00	35	86.36	89.40
09	20.32	23.36	16	38.10	41.14	26	63.50	66.54	36	88.90	91.94
10	22.86	25.90	17	40.64	43.68	27	66.04	69.08			
			18	43.18	46.22	28	68.58	71.62			
			19	45.72	48.76	29	71.12	74.16			
			20	48.26	51.30	30	73.66	76.70			

Ordering Codes

C FB8S217 - XX XX X XXX X X A X

No Of Pins Per Row
 04 - 36

Plating Code
 03 - Tin
 06 - Gold Flash
 09 - Gold Flash/ Tin

Material Code
 A - PBT

Pin Length (C/D)
 001 : B=3.20 / E=3.70 / F=8.50
 002 : B=3.20 / E=3.70 / F=6.50

Colour Code
 N - Black

Post
 W - W/O Post

Packing Code
 C - Tube

For special length requirement
Please contact our sales personnel

Due to technical progress, all designs, specifications and components are subject to change without notice.