


Specifications


Current Rating : 1.0 Ampere
 Insulation Resistance : 1000 MΩ Min
 Dielectric Withstanding : 300V AC
 Contact Resistance : 20 mΩ Max
 Operating Temperature : -40°C to +105°C

Materials






Contact Material : Brass
 Insulation Material : High Temperature Thermoplastic, 94V-0 LCP



Mating with



CFB5S201 CFB5S213



No. of Pins/Row	Dimension Information		No. of Pins/Row	Dimension Information		No. of Pins/Row	Dimension Information		No. of Pins/Row	Dimension Information	
	C	D		C	D		C	D		C	D
02	1.27	2.54	11	12.70	13.97	21	25.40	26.67	31	38.10	39.37
03	2.54	3.81	12	13.97	15.24	22	26.67	27.94	32	39.37	40.64
04	3.81	5.08	13	15.24	16.51	23	27.94	29.21	33	40.64	41.91
05	5.08	6.35	14	16.51	17.78	24	29.21	30.48	34	41.91	43.18
06	6.35	7.62	15	17.78	19.05	25	30.48	31.75	35	43.18	44.45
07	7.62	8.89	16	19.05	20.32	26	31.75	33.02	36	44.45	45.72
08	8.89	10.16	17	20.32	21.59	27	33.02	34.29	37	45.72	46.99
09	10.16	11.43	18	21.59	22.86	28	34.29	35.56	38	46.99	48.26
10	11.43	12.70	19	22.86	24.13	29	35.56	36.83	39	48.26	49.53
			20	24.13	25.40	30	36.83	38.10	40	49.53	50.80

Ordering Codes

C MA5N XX - XX X XXX X X B X

01 : H=2.54
03 : H=1.70

No Of Pins Per Row
 02 - 40

Plating Code
 03 - Tin
 06 - Gold Flash
 09 - Gold Flash/ Tin

Material Code
 C - LCP

Pin Length (C/D)
 CMA5N201 024 : A=3.80 / B=2.00 / E=2.50
 CMA5N203 003 : A=3.05 / B=2.54 / E=0.85

Colour Code
 N - Black

Post
 W - W/O Post

Packing Code
 C - Tube

For special length requirement
Please contact our sales personnel

Due to technical progress, all designs, specifications and components are subject to change without notice.